In the claims:

Please amend the claims as shown below:

1. (Currently amended) An arrangement for the axial driving of a supply hose (11) for pressure medium or application medium in the form of fluid, gaseous or solid, granule-formed or powder-formed, material, which supply hose (11) is connected to a displaceable cartridge (42) provided with at least one spray nozzle (43), which cartridge (42) is in turn arranged in a guide tube (41) along an ~~the~~ object that is to be sprayed, c h a r a c t e r i s e d in that the arrangement comprises three driving wheels (21), where at least one driving wheel is driven by driving means and where each driving wheel (21) has a concave jacket surface (27) congruent with the supply hose (11), where the concave jacket surface (27) surrounds the supply hose (11) and surrounds this to at least 100° degrees of the circumference of the supply hose (11).

2. (Currently amended) The arrangement according to claim 1, ~~c h a r a c t e r i s e d in that~~ wherein the driving wheels (21) are in physical contact with each other in such a manner that there arises indirect driving of the other driving wheels (21b-21c) driven by the first wheel (21a).

3. (Currently amended) The arrangement according to claim 2, ~~c h a r a c t e r i s e d in that~~ wherein ~~the~~ outer sides of the jacket surfaces (27) on each driving wheel (21) comprises teeth (28) which enter into shape-determined interaction with the teeth (28) of neighbouring driving wheel.

4. (Currently amended) The arrangement according to claim 2, ~~c h a r a c t e r i s e d in that the~~ wherein outer ends of the jacket surfaces (27) are plane and in that the driving wheels (21) have a coefficient of friction $\mu>0.8$ between each other ~~$\mu>0.8$ and preferably $\mu>0.9$~~.

5. (Currently amended) The arrangement according to ~~claims 1-4, characterised in that the~~ claim 1 wherein a contact pressure between the driving wheels (21) and the supply hose (11) is controlled by a ~~sprung~~ spring element (25).

6. (Currently amended) The arrangement according to claim 5, ~~characterised in that the sprung~~ wherein the spring element (25) is a pneumatic cylinder.

7. (Currently amended) The arrangement according to ~~claims 1-6, characterised in that~~ claim 1 wherein the supply hose (11) is rolled onto and out from a hose magazine (31).

8. (Currently amended) The arrangement according to claim 7, ~~characterised in that~~ wherein a pulley (32) is located at ~~the centre~~ a center of the hose magazine (31), which pulley is fixedly arranged relative to the hose magazine and rotates with the hose magazine ~~it~~, to which pulley a tension strap (33) is attached, where the tension strap (33) passes over a ~~sprung~~ spring element (34) and is fixedly attached at its outer end in a fixture (36) fixed in space, whereby the hose magazine is influenced by a force level (Fx) in ~~the~~ an opposite direction to a ~~the~~ dispensing direction (f) of the supply hose (11) from the hose magazine (31).

9. (Currently amended) The arrangement according to claim 8, ~~characterised in that the sprung~~ wherein the spring element (34) has a low force level (Fx) when the hose magazine rolls in the dispensing direction (f) and a high force level (Fx) when the hose magazine rolls in ~~the~~ a collection direction (b).

rf 128.1045PAT 23-Feb-04

10. (Currently amended) The arrangement according to ~~claims 8-9, characterised in that the sprung~~ claim 8 wherein the spring element (34) is a pneumatic cylinder.

11. (Currently amended) The arrangement according to ~~claims 1-10, characterised in that~~ claim 1 wherein a scraper (12) is arranged between the driving wheels (21) and the guide tube (41), with the purpose of scraping away any material deposited onto the supply hose (11).

12. (Currently amended) The arrangement according to claim 11, ~~characterised in that~~ wherein the scraper (12) comprises at least one sealing arrangement, which surrounds ~~and~~ the supply hose (11) in a sealing manner.

13. (Currently amended) The arrangement according to ~~claims 1-12, characterised in that~~ claim 1 wherein ~~the driving wheels (21), or only their~~ the concave jacket surfaces (27)~~,~~ are manufactured from a polymer material with a hardness that is equal to that of the supply hose (11)~~, or preferably lower than this hardness~~.